



OUTPUT VALUES

Standby Power	Voltage	230/400
Standby Power	kVA	33
Standby Power	kW	26
Standby Power	Amper	47
Prime Power	Voltage	230/400
Prime Power	kVA	30

Prime Power	kW	24
Prime Power	Amper	43

DIESEL ENGINE

Brand	PERKINS
Model	1103A-33G
Max. Total Output Pow. (kWm/hp)	30,4 / 40,8
Cylinder Displacement (lt)	3,3
Cylinder Orientation	3 Single Line
Bore x Stroke(mm*mm)	105*127
Compression Ratio	19,25;1
Governor Type	Mechanic
Rotation	1500 RPM
Aspiration System	Natural
Injection	Direct
Cooling System	Water Cooled
Electrical System(V DC)	12
Oil Capacity (lt)	7,9
Engine Coolant Capacity (lt)	10,2
Fuel Cons. %50 (lt/h)	3,9
Fuel Cons. %75 (lt/h)	5,4
Fuel Cons. %100 (lt/h)	7,1


ALTERNATOR

Standby Power (kVa/kw)	33/26
Prime Power (kVa/kw)	30/24
Brand	MECC ALTE
Output Voltage (V)	231/400
Frequency (Hz)	50
Stationary Vol. Regulation(±)	0,01
Short Circuit Current	%300 (10 sec)
Insulation	H
Protection	IP23
Efficiency (%)	92
Overloading	110% for 1 hour
Power Factor (cos Q=0.8)	0,8
Tot. Harmonic Dist. Rate	<1 %
Connection Type	Star
Number of Pole	4
Number of Bearing	Single

DIMENSIONS & WEIGHT

Without Canopy	Width	1000 mm
Without Canopy	Length	1800 mm
Without Canopy	High	1500 mm
Without Canopy	Weight	736 kg

Without Canopy	Fuel Tank Capacity	180 lt
With Canopy	Width	1000 mm
With Canopy	Length	2150 mm
With Canopy	High	1650 mm
With Canopy	Weight	1050 kg
With Canopy	Fuel Tank Capacity	180 lt



**MADE IN
TURKEY**