Trio GENERATOR

MOTEURS Baudouin



MADE IN TURKEY

International Organization for Standardization ISO 14001:2015

ISO 9001

CE

OUTPUT VALUES

Standby Power	Voltage	230/400
Standby Power	kVA	220
Standby Power	kW	176
Standby Power	Amper	198
Prime Power	Voltage	230/400
Prime Power	kVA	200
Prime Power	kW	160
Prime Power	Amper	288

DIESEL ENGINE

Brand	BAUDOUIN
Model	6M16G220/5
Max. Total Output Pow. (kWm/hp)	220/200
Cylinder Displacement (lt)	9,72
Cylinder Orientation	6 Single Line
Bore x Stroke(mm*mm)	126 x 130
Compression Ratio	17:1
Governor Type	Electronic
Rotation	1500 RPM
Aspiration System	Turbo AAC
Injection	Direct
Cooling System	Water Cooled
Electrcal System(VDC)	12/24
Oil Capacity (lt)	24
Engine Coolant Capacity (lt)	90
Fuel Cons. %50 (lt/h)	21
Fuel Cons. %75 (lt/h)	31
Fuel Cons. %100 (lt/h)	42

ALTERNATOR

Standby Power (kVa/kw)	220/176
Prime Power (kVa/kw)	200/160

Brand	TRIO
Output Voltage (V)	230/400
Frequency (Hz)	50
Stationary Vol. Regulation(±)	0,01
Short Circuit Current	%300 (10 sec)
Insulation	H
Protection	IP23
E ciency (%)	92,7
Overloading	110% for 1 hour
Power Factor (cos Q=0.8)	0,8
Tot. Harmonic Dist. Rate	<2 %
Connection Type	Star
Number of Pole	4
Number of Bearing	Single

DIMENSIONS & WEIGHT

Without Canopy	Width	1100 mm
Without Canopy	Length	2500 mm
Without Canopy	High	1650 mm
Without Canopy	Weight	2300 kg
Without Canopy	Fuel Tank Capacity	280 lt
With Canopy	Width	1100 mm
With Canopy	Length	3100 mm

With Canopy	High	1900 mm
With Canopy	Weight	2625 kg
With Canopy	Fuel Tank Capacity	280 lt